

Entered at the Post-office at Hillsboro, Oregon, as Second class mail matter.

LUCIUS A. LONG, EDITOR.

County Official Paper.

Subscription: One Dollar per Annum.
Six Months, 60 cts; Three Months 35 cts.

ISSUED EVERY THURSDAY

Long & Robinson.

UNION PARTY CALL.

The Union Party County Convention will be held at the Court House at Hillsboro, Oregon, on Thursday, the 14th day of April, 1904, at 1:30 p. m., for the purpose of electing nine delegates to attend the State Democratic Convention at Portland, Oregon, on the 19th day of April, 1904. The following appointments have been made as delegates of the several precincts, to-wit:

Beaverdam.....	9	East Butte.....	4
Beaverton.....	9	Gales Creek.....	4
Buxton.....	7	Mountain.....	4
Cornelius.....	12	N. Hillsboro.....	11
Columbia.....	12	S. Hillsboro.....	10
Daily.....	14	S. Forest Grove.....	12
Dillie.....	7	S. Forest Grove.....	9
E. Cedar Creek.....	8	South Tualatin.....	10
W. Cedar Creek.....	8	Wapato.....	10
West Butte.....	7	Washington.....	12
Reedville.....	12		

The date of the precinct meetings is recommended for April 7, 1904.

JAMES H. SEWELL, Chairman.

JOHN M. WALL, Secretary.

Argus and Oregonian, \$2.00.

Mrs. Frank Taylor, aged 42, died Sunday at the family home on the Butler donation, east of town. She leaves the husband and one son.

Remember the dance at the W. O. W. Hall, Cedar Mill, Saturday evening, April 9. Tickets, \$1.00. Walkers' orchestra. Everybody invited to attend.

The Modern Woodmen and Royal Neighbors held a social at Wehrung's Hall last Saturday evening and a very pleasant time was enjoyed by those present.

Mary E. VanBlaricom has sued Harvey VanBlaricom for divorce, alleging desertion. The couple were married at Vernonia several years ago, and there are four minor children. The defendant demurs to the complaint, alleging insufficient cause for the action.

L. E. Wilkes, U. S. Examiner of Surveys, and who is here on a furlough, visiting with his family, leaves the first of the week for Boise, to which place he has orders from the Department of the Interior. He will spend several weeks looking over Idaho lands and their availability for agricultural purposes.

Willis Caudle the eldest son of Mr. and Mrs. Thos. Caudle, and aged about 10 years, died last Monday. The little fellow was a sufferer from scarlet fever. The parents have the sympathy of their many friends. The funeral took place yesterday morning, interment being in the Hillsboro cemetery.

REPUBLICAN PRIMARIES.

Today is republican primary day over Washington county. So far as heard from the election of delegates is:

North Hillsboro—J. W. Bailey, C. Shaner, W. V. Wiley, Thos. Burck, (elected on contest by about four majority) W. D. Smith, S. Galloway, E. C. Brown, T. K. Imbrie, A. Hartman, Herman Kauna, these last six being elected by acclamation. H. T. Bagley was nominated over W. D. Smith, for justice, by a vote of 39 to 31.

South Hillsboro—B. P. Cornelius, John Milne, Thos. H. Tongue, J. W. Morgan, R. J. Lyons, John Johansen, Frank Pauli, Willis Anderson, H. D. Schmelzer, W. J. Benton.

Beaverdam—Erwin Ritter, C. Schindler, Fred Hamel, N. Johnson, G. Zurcher, F. Berger, J. Q. A. Young.

Cornelius—G. B. Buchanan, G. W. Marsh, Fred Schoen, Jr., C. Hancock, W. B. Slaughter, C. F. Meyers, Albert Bunning, C. W. Fitch, L. Holtz.

Dillie—A. Briggs, W. W. Lewis, A. Dethlefs, Wilbur Hughes.

East Butte—E. J. Godman, F. Elmer, Oliver Galbreath, F. Gault, H. E. Figgard, A. W. Smith, J. Hobman, C. F. Tigard, A. Zwiener.

East Cedar—Geo. Nyberg, J. Martazzi, Jno. Hedges, E. Savage, Jno. Day, L. P. Spencer, A. Kriger, E. A. Rddy.

South Tualatin—J. H. Collier, F. H. Simpson, J. J. Krebs, Grant Mann, J. S. Robinson, H. R. Emmott, W. H. McCormick.

Gales Creek—W. P. Shearer, J. McRobert, Jno. McClaran, J. Martin, Chas. Staley, W. P. Clapham, J. Bots.

Columbia—Alec Gordon, C. Nelson, E. P. Cornelius, J. C. Corey, Wm. Bagley, E. S. Schaffelin, John Davis.

Gaston—G. Meisner, H. L. Russell, R. Matieson, J. Hill, E. X. Harding, C. C. Newman, V. Calhoun, B. F. Parley.

West Butte—Ole Olson, C. P. Hesse, A. N. Davies, L. Bierly, A. F. Robinson, A. N. Cutting, C. VanKleeck.

Buxton—Geo. Holt, Alfred Stevens, D. Cummings, C. W. Hines, F. H. Duxton.

Beaverton—H. G. Vincent, Al. Davis, Mel. Barnes, M. D. Cary, W. J. Butler, John Johnson, C. W. Allen, C. Rosander, W. E. Squires, Theo. Pointer.

Washington—Wm. Bachelder, John Connell, Henry Kurall, L. Tompkins, J. W. Goodin, W. Jose, Jasper Keffer, M. C. Lincoln, A. Guerber.

North Forest Grove—L. E. Smith, W. R. Harris, B. H. Laughlin, W. A. Lillingher, H. T. Duxton, J. C. Clark, R. M. Taylor, A. T. Buxton, J. T. Fletcher, J. C. Giltner, David Smith.

South Forest Grove—Messrs. Watrous, McNamee, Wm. Leach, D. C. Stewart, Walter Hogg, King, T. G. Todd, J. A. Thorburgh, S. G. Hughes, S. Starrett, John Baldwin, F. T. Kane, A. W. Mills.

Reedville—Geo. Jack, John Borwick, Julius Weisenbach, E. P. Keeder, E. W. Hunt, C. E. Lester and James Macnaman.

Daily—H. C. Carstens, W. L. Moore, J. L. Keris, J. F. Carstens, W. H. Baker, J. Herb, J. Becker Jr., J. B. McHenry, J. S. Benedict, O. L. Ahlstrom.

Mountain—Leo Schwander, T. G. Meacham (Probable).

West Cedar—St. wart Vaughn, J. A. Chapman, L. F. McCormell, F. Westphal, A. Stein, R. G. Hagey, A. A. Canfield, S. Craven.

Indications are that the Mitchell wing loses the county and that the control is now in the hands of B. P. Cornelius and his colleagues.

William Reid, the old Astoria & South Coast Railroad promoter, is just now filling Portland's dailies with articles telling that he now has Eastern money pledged to build a road from Portland into the Tillamook section provided that Tillamook county will give the right of way free of charge. He says if Tillamook does not give the right of way, the line will go into the Nehalem section and cut out the Tillamook survey. The proposed Tillamook route would leave Hillsboro, where it is scheduled to connect with the Southern Pacific, and this would give a large portion of Washington county a railroad line that now brings its traffic to the Southern Pacific line. The Argus hopes that Reid's statements are true—that he has the money pledged and it is also to be hoped that Tillamookers will give the right of way. The contention seems to be from the Tillamook standpoint, that if they give the right of way the terminus of the line should be their county seat, while Reid does not want to be tied to the proposition of building no farther up the coast.

NADERER-LARSON.

Mr. Anton Naderer and Mrs. Mary Larson were married at the bride's home at Laurel, Tuesday, March 29, at high noon. Rev. Locke of Seaford, Mrs. P. N. Vibbert was matron of honor and Miss Martha Ritter was maid of honor.

Only immediate relatives and a few intimate friends were present. The guests were as follows: Mr. and Mrs. A. Vibbert, Mrs. P. N. Vibbert and son, Mr. and Mrs. Julius Christenson, Mr. and Mrs. Mike Ritter, Mr. Christenson, Misses Martha Ritter, Clara and Emma Vibbert and Mr. Elmer Christenson.

Many valuable presents were given them.

PROBATE.

Estate Phil Baughman, deceased; executor allowed funeral claim of \$62.50.

Philomena Perrett, feeble in mind; April 12 set as date to hear petition why guardian shall not be appointed.

Estate James P. Lilly, deceased; F. M. Francis, Sr., James McClaran and Carl Her appointed appraisers to meet April 9 and value estate.

GRANGE RESOLUTIONS.

Washington Grange, meeting at Arcade school house, passed the following resolutions at a recent meeting:

Whereas Death has invaded our Grange and removed from our ranks Brother Perry R. Miller, therefore, be it Resolved, That as this Grange has lost a worthy member in the death of Brother Perry Miller, we, as members of Washington Grange No. 313, extend our sincere sympathy to the bereaved family.

Resolved, That our charter be draped in mourning for thirty days and that a copy of these resolutions be presented to the bereaved family, and spread on the records of the organization, also copies furnished the county papers and Grange Bulletin for publication.

(JOHN LOFTIS
Committee—SARAH H. HARVEY
(A. E. MCCUNEY)

REAL ESTATE TRANSFERS.

Wm Wolf to E A Wilkes q c lot 3 b k 1 Thorne's ad	\$25
R C Hill to T A Ritchey w 1/2 lot 3 b k 42 Forest Grove	1000
Zeraiah Large to E Stella Watson 56x120 lot 1 b k 2 F Grove	800
Chas Frickett to Grace Frickett 40 x sec 13 1/2 r 4 w	400
Guy Delano to M W Wilkins 76 x sec 17 1/2 r 3 w	1600
M W Wilkins to John Dement same as above	1600
State to H W Price, 80 x sec 36 1/2 r 4 w	100
James Keeney to James Frainey, lot 18 sec 24 1/2 r 1 w, 10 acres F D Culver to H A Hinshaw the Pence lot, near depot, Hillsboro	1
Claude Greear to W G Hager lots 4 5 6 b k 17 Simmons' addition, Hillsboro	450
Thos Talbot to W H Rogers lots 8 9 and 10 b k to Cornelius Farmington Creamery Co to John Halverson 1/2 acre Farmington Creamery site	250
C K Henry to A S Sholes lots 4 5 6 7 8 and 9 b k 14 Simmons' ad Hillsboro	575
Ursula Yager to C K Henry lots 7 8 and 9 b k 14	200
C L Large to A M Staehr 56x120 lot b k 25 Forest Grove	900
John Chalmers to Alec Chalmers tract in sec 8, 9, 16 and 17 1/2 r 3 w	1200
Martha A Miller et als to Preston Richardson lots 1, 2, 8, 9, 10 b k 5 Purdy's ad, Dillie	500

"LET DOWN YOUR BUCKET WHERE YOU ARE."

EDITOR ARGUS: Two things have impressed me since the publication of my letter on the highway, in your paper of the 17th. They are the exasperation of the public on the condition of the roads, and the evidently great circulation of the Argus—considering the number of people who have hailed me on the subject. All agree that better ditching must be done, for everyone knows that a wet road bed is a bad one. I have been glad to see various districts preparing to employ the services of these most valuable public servants, ditchers and ditchers—the latter faithfully working slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless as a pair of scissors with one blade. The road must gently slope to the ditch, to aid itself of the rain water, and its edges must be rounded so that the water easily gets off the road into the ditches. A sloping edge is also less liable to fall in and obstruct the ditch. If they and the roads are properly constructed, a ditch at one side only of a road is often as useless