### CITY NOTICES.

ORDINANCE NO. 316.

An ordinance amending section 2 of ordinance No. 129, providing for the notification of the city librarian of any contagious disease present in the city.

as follows:

city physician shall be as follows: the board of health, but subject to its vertical lines;

directions. infectious diseases He shall attend all persons re-

ance, who may for the time being be in charge of the city

other physicians, or other persons of

of the person afflicted, and addressed to the city librarian of the city of Medford.

The above ordinance was passed this 15th day of March, 1910, by the following vote: Welch absent, Merrick aye, Emer-

Demmer ave. Approved by the mayor March

16th, 1910. W. H. CANON, Mayor Attest: ROBT. W. TELFER. City Recorder.

## ORDINANCE NO. 811.

An ordinance regulating the plumbing, ventilating and drainage of buildings, and to provide for the reglatration of plumbers. The city of Medford doth ordain as

follows:

structure, dangerous or prejudicial to building or areas. Every person engagregistry upon presenting satisfactory charge from water closets.

DEFINITION OF TERMS Section 2. The term "private sew- low the surface of the ground. is applied to all sewers that are

The term "house drain" is applied | teen

with or without other fixtures.

The term 'branch vents" is applied to the main vent. The term "unsanitary" is applied

to the following: To any fixture whose trap does not MATERIAL AND WORKMANSHIP. Section 5. All material must be of maintain a proper seal

To any fixture not having a proper or sufficient water supply to thoroughly flush it out and keep it in a thorough and workmanlike manner. clean and wholesome condition. To any drain, soil, waste or vent pipe which is not gas tight or emits

any foul or obnoxious odors. pipe that is stopped or partially stop-

containing a foul odor.

To any imperfect fixture, pipe or To any work not conforming with the rules of this ordinance.

To anything which is detrimental to health. The term "drainage work" is ap-

plied to the house sewer and house drain and its horizontal branches col- 4-inch, lectively or separately. The term "plumbing work" is ap- 6-inch.

plied to all fixtures having a waste 7-inch. outlet from them to the branch waste 8-inch, from them to any vertical soil, waste or vent pipe.

SOIL AND WASTE PIPE. Section 3. In every building where 4-inch, there is an interior or exterior water 5-inch closet there must be at least one four- 6-inch. inch pipe extended through the roof, 7-inch, No closet soil pipe shall be less than 8-inch, four inches in diameter. When twelve or more water closets are connected to one soil or drain pipe, said soil and fittings.
or drain pipe shall not be less than LEAD TRAPS AND WASTE PIPES. en from the main six-inch soil or the drain pipe carried up to and through follo the roof will be considered equal to one six-inch vent.

Branches for water closets shall Hasis not be less than four inches in diam- Kitch eter and where vertical lines of soil Bath pipe extend to water closets on sec- Slop ond floor, must extend full size Urinals ..... 1 1/2 inches

#### CITY NOTICES.

through roof. Lines of waste pipe in buildings with either one or more for waste pipe vessels, other than water closets, connected thereto, shall be at least three

through roof two (2) feet. Waste pipes shall be of cast fron inches in diameter with four-inch waed littings shall be used for horizon- full size of trap. All traps for bath where lead traps are ed by means of a wiped solder joint. HOUSE DRAINS

Every house or building hereafter quiring medical or surgical assist- connected to public sewer or private cesspool, shall have the house drain through which sewerage is carried 4. He shall immediately report to constructed of cast fron pipe, which the city librarian any contagious dis-shall extend five feet outside of Such notices shall be in writing shall have proper fall of not less than shall be screwed joints. as straight a line as possible, All joints, with standard iron means of Y branches and one-eighth extra heavy brass caulking, ferrules shall be made jointing cast fron pipes pipe. Approved combination ferrules ick aye, Wortman aye, Elfert aye, together, but shall be made with required fittings and bends. Sanitary shall be used only in vent pipes. tees shall only be used in vertical lines of pipe. Heel outlets shall not Plange joints connecting lead pipes used for vent connections. There shall be a cleanout put in the house concealed, are prohibited drain at the last change of direction

to basement level from Y branch.

TERRA COTTA SEWERS. after erect or cause to be erected any building or shall any builder, lessee, hundred feet of a public water sup- flashing at least two inches building or convert any building to tenant or occupant of any building, ply, the water closet and sink drains a new purpose, by alteration, by ad-nor any plumber or person or per-shall be connected vila cesspools, dition or otherwise, so that it or any sons interested in the plumbing work which shall penetrate the gravel strata part thereof shall be inadequate or about such building, allow any terra at least five feet in depth, and said defective in respect to plumbing, ven- cotta sewer to be laid within alve feet cesspool shall be walled up with tilation or sewerage, or any other of such building, and in all cases be-usual, proper or necessary provisions fore a new or old building is placed ness and arched over at least three means of a shaft or air duct, at least vision in this ordinance, or where the or precautions for the security of life or remodeled on any lot which has a feet below the surface of the ground six inches in diameter, or of equal connections arise that demand the examination shall consist of sanitary or health, nor shall any owner, build- terra cotta sewer which would come and ten feet from any ballding, the area, and as near the celling as possi- discretion of the inspector of plumber, lessee, tenant or occupant of any under any part of the foundation, arch to be laid with good cement building or structure cause or allow said sewer or terra cotta pipe, must mortar. No person or persons shall roof or to the hot air flues above all tor may give in writing to the owners must be replaced by iron sewer which must within the corporate limits of the city openings. in or about any such building or be extended five feet outside of the

Terra cotta sewers running paraled in the plumbing business in the lel with any building and within ten city of Medford as a master plumber feet must be laid two (2) feet below or any other person coming from oth- the foundation or level of the baseer cities as a master plumber shall ment floor. Where it is impracticaappear in person at the office of the ble to do so, cast fron pipes must be inspector of plumbing and register laid. All terra cotta sewer pipe used his name and business address, upon for house drainage in the city of Medforms prescribed by the board of ex- ford shall be not less than six inches aminers, and receive a certificate of in diameter where used for the dis-Three proof that he is a bona fide master inch terra cotta sewer pipe may be plumber: and no person other than a used for wastes from small fixtures. registered plumber shall be allowed but must be thoroughly vitrified unio carry on or engage in the plumb- form in size, straight and free from be ventilated by an air pipe. In cases run into vent horn of trap used for writing, notify the inspector of plumbing business or make any connection defects, and laid in trenches in as where the size of trap is two inches drains, said trap shall never be placed ing and drainage that work is ready with any sewer drain, soil waste or straight lines as possible, with a fail or less, the vent pipe shall start not in the main running line of drain or for inspection, he shall within sixmore than four inches away from the waste pipe, but shall be connected to the foot where possible, and water line of traps, except P traps with a Y branch fitting.

All joints shall be made with equal not constructed by and under the parts of the best Portland cement and provision of the city of Medford. The clean, sharp sand; each joint shall be trap and vent pipe. "house sewer" is applied to that carefully cleaned on the inside when part of the main drain or sewer ex- it is laid; the cement must be pressed from top of waste or crown of trap, shall never be placed in the main run- pipes are tested and securely strapped tending from a point five feet outside into the hub and beveled outside the and where changes are made in di- ning line of drain or waste pipe, but in place, with iron hangers made of such fee has been paid of the outer wall of the building, socket and made smooth and solid rections of vent pipes below the top shall be connected with a Y branch not less than one-quarter-inch iron, and left uncovered until examined of fixtures shall be made at an angle litting.

PENALTIES.

PENALTIES.

Section 23. It shall be unlawful and that the following is the public sewer, private sewer or cess- by the inspector of plumbing, said of not less than 45 degrees. No hori- FIXTURES AND HOW TRAPPED. to that part of the main horizontal fied. It shall be unlawful for any Where possible the branch tees of independently trapped. to that part of the main horizontal fied. It shall be unlawful for any Where possible the branch tees of independently trapped. The traps until said building or buildings are ford, and any person violating any of gen, amending said sub-section 42 of drain and its branches inside of the person to lay sewer pipe to connect vent pipes shall not be less than one shall be as near as practicable to the connected with the public sewer or the provisions of this ordinance shall, section 25, and section 100 of said walls of the building, vault or area any building with a public sewer, or foot above the top of fixtures, All fixture it serves; no fixtures, and the water perupon conviction thereof, be fined in charter, fixing the time for which conextending to and connecting with the private cesspool, or construct cesssanitary fittings being used for vents set unless sceppiled with sufficient mit signed by the inspector of the private cesspool. The term 'soll pipe" is applied to bona fide master plumber, or by ob-any line or pipe receiving the dis-taining a permit from the inspector nects closet to cast iron, there must barber shops or office buildings are charge of one or more water closets of plumbing and drainage, to con- be at least lifteen inches of two-The term "vent pipe" is applied sewers as may be put in under the No pipes or sewer side of trap seal.

erty lines. When terra cotta sewer under any to the branches from the fixture trap building becomes defective it must be replaced by an iron sewer, no terra cotta pipe shall be connected into single fixture, on vertical line of soil tron pipes on any premises.

> good quality and free from defects and the work must be executed in a

STRENGTH OF SOIL PIPE. The cast fron soil pipe and fittings must be sound and free from holes and cracks and of a grade known To any drain, soil or waste or vent in commerce as extra heavy. Provided, however, that in the case of oneany water closed apartment of buildings having two or more stohas the floor saturated with urine or as standard may be used. Provided further, that whenever a soil pipe shall run beneath the basement floor of any building the extra heavy must be used. The following weight per lineal foot will be accepted as com-

plying with the ordinance: Extra heavy-5 1/2 pounds per lineal foot 2-inch. pounds per lineal 3-inch. foot pounds per lineal foot pounds per lineal 5-inch foot pounds per lineal 33 14 pounds per lineal foot

Standardpounds per lineal foot 2-inch. 3-inch. pounds per lineal pounds per lineal 10.36

best quality and not less than the		it receives		the sev		reral a	dditto
wing weight per lineal fo	Sizes.						Weig
er closets 4	inches	4	inches	5		pounds	per
ns and pantry sinks 1 16	inches	3.	Inches	4	Me	pounds	per
hen sinks	Inches	2	inches	4		pounds	per
and laundry tubs 1 14	Inches	1.56	inches	3		nounce	per
sinks	inches	1.54	inches	- 2	14	pounds	per
11/	Inches	1000					

#### CITY NOTICES. CITY NOTICES.

All bath tubs trapped with a drum est fixtures, which soff pipe must be sheet metal than copper or brass trap of lead or brass shall have flange of ample size or be increased; these shall be used for urinals. Urinals sist of the inspector of plumbing and have been approved. One set shall inches in diameter extended full size set flush and secured to finished air pipes and fittings must have a in all public ; aces an I buildings drainage, and also two master plumb- be retained in the office of the infloor; trap shall not be less than four continuous fall to drain all water shall be automatically flushed at ers and one journeyman plumber, ap- spector of plumbing for reference or lead and shall not be smaller in ter weal set clear of tub with standline duties of the health offcer and diameter than traps used. No threadlameter than traps used. N old work is repaired black vent pipes, He shall be executive officer of tal waste pipes, but may be used in tubs shall have heel of trap reinforc- if in partition running direct to waste pipe and found in good condiused threaded fittings shall be one No trap screws shall be concented tion and size required, may remain, which is used as a dwelling, but directions.

2. He shall visit and examine all persons sick, or reported or suspect-persons sick, or reported or suspect-p ventilator. barber shops shall be trapped by

TERMINALS OF VENT PIPES. drum trap with at least six-inch water seal, if not vented, and shall be not The terminals of all vent pipes must be at least two feet above any less than four inches in diameter. air shaft or window, or twelve feet JOINTS AND FERRULES. Joints in east fron pipes shall be away from the same and two feet made with pure lead an : picked oak- from the terminus of any chimney enses of which he may actually know, building or foundation line. The made with pure lead an picked oak- from the terminus of any chimney or which may be reported to him by drain to be laid in trenches of uniform grade or suspended from floor nish or putty allowed in caulking said [main roof. Vent pipes when not timbers by strong iron hangers; they loints, Joints I: wrought iron pipes twelve feet from window or other Joints in openings must be combined. and shall give the name and address one-quarter of an inch per foot where brass or lead pipe shall be in all where possible connected to the main blowoff or drop pipe shall not be possible towards the main sewer and cases wiped solder joints or screwed vent stack below the roof of the pipe In as straight a line as possible. All thread. Joints between lead and iron extend more than three feet above the with any rain water conductor. Steam changes in direction or connections to thread. Joints between lead and from changes in direction or connections to thread. Joints between lead and from roof of any building, except outside shall be discharged into a blowoff or soil or waste pipes shall be made by pipes shall and one-sixteenth bens. No angles or solder nipples, the full size of the the building. or within twelve feet of another main drain. may be used only where said ferrules having are outside of building. Double hubs building of greater height.

ROOF FLASHING

ROOM VENTILATION.

never be placed in an unventilated

room or compartment. In every case

the compartment must be opened to

RAIN DRAINS.

in which case they shall be drained

into house drains by using an in-

FLOOR DRAINS.

WATER CLOSETS.

WATER CLOSET TANKS

WATER CLOSET FLANGES.

Section 6. All drains from conduc-

Water closets and slop sinks must

fectly water tight by means of

All pipes running through the roof

together, or lead and brass, where All brass ferrules shall not be less or at the end of the main horizontal than four inches long. The discharge carried up above the eaves or fire niently shut off and drained from the ine in the building. All cleanouts from elevators, if not over two inches shall be closed by brass serew covers in diameter, shall be connected direct shall be no caps, cowles or return be so arranged as to drain towards ship may pass the examination and the 16th day of March, 1910, by the with not less than six threads of iron to the main sewer in the street, and bends put on the end of any vent pipe. the stop and waste cock, or to fixpipe, standard thread and shall be under no conditions shall they kept accessible; when drains are laid connected to sewe; or drain from of any building shall be made per-

beneath the floor, cleanouts shall run any building CESSPOOLS AND CONNECTIONS. Section 6. In all cases where a new of Medford erect or maintain, or suffer to be erected or maintained upon any premise; owned by him, her any lot or parcel of land abutting cept when grades will not permit, upon any street in which there has

tained a public sewer VENTILATION. Section 7. All waste pipes must be shall be not less than two feet be- and drum traps, which shall be not more than twelve inches from water line in trap, providing there is not sewer shall be trapped with a deep he shall issue a proper certificate to

cen constructed and is being main-

All vent brenches must be taken pools except under the direction of a must be inverted. In cases of larger water to properly flush it. struct cesspools except such lateral inch lead pipe on vent connections. some accessible point for connection when fixtures are set. The highest pipe and within two feet of the same, need not be back vented, tures may be connected to lead bend, providing they connect above the cen-

The vent or air pipes from traps thirty feet or minimum thereof; not with bowl forming a seal. When al- when, in his judgment, the plumbing of not lessthan ten dollars or more legal voters may see fit. No franventilated from a one and a quarter- said closets must be removed and a unsanitary, he shall have the power story buildings and in the upper story inch pipe or more than four from a tank closet substituted. one and one-half-inch pipe, or more which is not thoroughly ventilated or ries, the grade known in commerce than eight from a two-inch pipe Not or wash bowls with wooden casings require the ventilation and drainage more than one water closet, includ- shall not be permitted. ing four small fixtures, can be venthan two water closets and two small fixtures. Not more than three water be vented from a two and one-half- sex or minimum thereof, pipe, or four closets and four small fixtures can be vented from a cases. Every tenement or lodging three-inch pipe or eight closets and house shall be provided with one waeight small fixtures. Nine or more ter closet for every ten rooms or min- bis office, and open to inspection by than the previously described amount pounds per lineal foot of fixtures may be ventilated by in- floor. creasing vent pipes in proportion to accommodate the desired amount of with at least one water closet and one specified, he or they shall be liable plumber, or other person, if a job of fixtures. When two fixtures are not sink. set back to back and traps serving pounds per lineal foot same are not over twelve inches from same are not over twelve inches from Every water closet in a building and any owner, agent or tenant shall the vent said traps will not be reshall be supplied with water from be jointly and severally liable therefoot quired to be back vented, provided pounds per lineal foot main waste and vent in one size largpounds per lineal foot er than traps used, excepting water at least four gallons at each flush- said notice, they shall be liable to re- the city treasurer and receive a repounds per lineal foot closets, which may be two feet from ing and shall have a flush pipe not arrest and like fine for each day celpt for the same. The size, weight and maker's name the main four-inch stack, vent to ex- less than one and one-quarter inches thereafter.

must be cast on each length of pipe tend full size through roof or to main in diameter. vent Air nines may be corebined by

> foot foot

# . CITY NOTICES.

No wrought iron pipe shall be used the size above specified, and may be to moisture, that will not corrode un- spector of plumbing or deputy inspec- and plumbing, and the city engineer connected to soil pipe above the high- der the action of urine, and no other tor of plumbing. formed by condensation. All vent least once each thirty minutes. Section 12. No wooden sinks or

ed in any residence or tenement work, and shall issue a certificate to allowed on the premises REFRIGERATOR WASTE PIPES.

cle where food is kept, shall be conwaste pipe; waste pipe shall not be meet on the second Monday of each to be properly flushed. STEAM EXHAUST.

Section 15. Any steam exhaust, connected directly with the sewer, building. Vent pipes in no case shall house drain, soil or waste pipe, or overflow from said tank shall be pro-When one building is attached to vided with a suitable outlet to the ing in such business, make application of the provisions of this ordinance for examination to the board of exam- where no penalty is provided, shall

WATER PIPES. windows or openings overlooking the lower building, the terminals of all must be provided with a stop and vent pipes of the lower building must waste cock, easily accessible, placed least twelve feet distant from beyond damage from frost and so sitsaid windows or openings, or shall be uated that the water can be convewalls of the higher building. There pipes. All pipes of the building must All water pipes shall be either galvanized iron, lead or brass. Hot water pipes must in all cases, where possible, run overhead and drop down or copper flashing to be caulked into to fixtures, so as to avoid trapping. REGISTRATION.

Section 4. In no case shall terra drainage and water closet accommoliave counter flashing running from one foot and six inches long and shall determined by the section of the placed at the termination of all section in the section of the placed at the termination of all section in the section of the placed at the termination of all section in the se building is erected, or where house hub of soil pipe, and if no hub, must Air chambers shall be not less than joints shall be wiped on lead connections.

SPECIAL PERMITS Section 17. When special fixtures or traps are required by owners or ble, and carried hence through the ing, upon examination, to the inspecer or architect a permit, if, in his work in plumbing and the correction judgment, the conditions demand the of defective plumbing work on plans, use of such fixtures or traps, provid- and a general knowledge of sanitary tors of rain water from roof shall be ing anti-syphon traps are used as ap-

TESTS AND INSPECTIONS. Section 18. When plumbing work tercepting deep seal trap which shall is sufficiently advanced in any buildbe extra heavy cast iron, on the house ing for inspection, all soil, waste, side of the trap seal, standard east drain or air pipes from a point of size of trap, excepting water closets, with fresh water from the nearest ter and if no water can be obtained All floor drains when connected to as prescribed by the city ordinance.

plumbing. combined together in one place, one trap may be used at the center ba- ing and drainage shall have the powsin, providing waste pipes connecting or in all cases where there is a build. for each day thereafter, and subject to any special pipe provided to ven-tilate the system of piping and to prevent the traps siphonage and back such laterals extend inside the prophave earthenware or fron enameled adjoining such street or alley, his flushing rim, eval bowds, flushed agent or tenant, to make sufficient from separate tanks. "Pipe wash" drain and proper sewer connections bowls or short hoppers, with traps for his or her house, yard or lot, clos- any such plumber or other persons chise granted by it for a ter line of bend and are vented to above floor will not be permitted on et or premises, whenever, in his opin-conform with section 7. any premises, or any closet bowl connected directly with, or flushed from he shall have the power to examine ing in which they have been placed pose of supplying gas to the city or exceeding thirty-five feet must be in- the water supply pipes, or any closet all buildings, as to the plumbing. creased one size every succeeding having any mechanism in connection drainage and ventilation thereof, and more than two small fixtures can be tered or when they become offensive. fixtures are found to be defective or to order their removal or repair, or Enclosing of water closets, sinks substitution of other fixtures and to distinct offense. of such buildings to be placed in a In factories and workshops where sanitary condition and he shall theretilated from a two-inch pipe, or more there are fifteen persons or less of upon give the owner, agent or tenant, each sex there shall be provided one or person occupying the building or within water closet for each sex and one for closets and eight small fixtures can every additional ten persons of each ing the time when any defective all

premises, notice in writing, specify- hours drain, sewer connection or unsanitary Toilets shall be separate in all plumbing fixtures must be completing, and the same presented to the few dimes. Isn't there something ases. Every tenement or lodging ed. He shall keep copy of such no-office of the water department, betice in a book which shall be kept in imum thereof, and one sink for each the public during his office hours. If said agent, owner or tenant neglects thorized and directed to collect a fine All residences shall be provided to complete the same within the time of one dollar from any registered to a fine of not less than ten dollars, nor more than one hundred dollars. a separate tank or cistern, which for; after conviction for one offense, shall be arranged so as to deliver if they shall refuse to comply with

> PLUMBING INSPECTOR AND BOARD OF EXAMINERS.

Section 20. The plumbing inspector All water closets, earthern or iron, ens to not less than one-eighth of an inch drainage, or

# CITY NOTICES.

pointed by the mayor of the city of tions theoretically and practically, to tendance at his office during the folwash trays will be allowed to be plac- construct and supervise plumbing lowing hours: each applicant passing a satisfactory examination, who shall thereafter be all plumbing and drainage inside of the ries and in kitchens of hotels and known as master plumber. All approperty lines, before the same is petal, restaurants. Wood lined sinks or plicants shall pay a fee of ten dol-covered. If, on examination of said wash trays or bath tubs shall not be lars for each examination. In case work, he finds the requirements of an applicant fails to pass the requir- this ordinance violated, he shall reed examination he shall be entitled port the same to the master plumber, Section 14. No waste pipe from to the return of the ten dollars, but verbally or in writing. If he finds no a refrigerator or any other recepta- he shall not be eligible for a second such violation, he shall take examination within six months there- tificate of approval to the master nected direct to any sewer, soil or after. The examining board shall plumber. less than one inch and so arranged as month so as to arrange for examin- ing will act in conjunction with the ations or other business and shall inspector of plumbi tions. The percentage required to pass said examination shall be not turn over all moneys he may receive

> in the business of plumbing in the the amount of money collected.
>
> city of Medford shall, before engag- Any person who shall violate two or more persons are engaged in fense. the plumbing business as co-partners. member of the firm, or co-partnerqualify for said firm or co-partner- following vote: ship. All persons or firms applying for registration must file with the in-spector of plumbing and drainage the mer aye. certificate of the board of examiners, approving their qualifications to conduct a plumbing business, and must have a permanent place of business. When a registered plumber, or the member of the firm who has pass ed the required examination, retires from business or dissolves co-partnership he shall forfeit his or their license and no other license shall be issued to him or said firm until he or they have passed said examination before said board of examiners. The of problems in, and execution of practical workmanship in plumbing, or theoretical questions, and practical plumbing, and shall be in writing on

TION OF PLUMBERS.

LICENSE Section 22. Each person or firm shall pay a license fee of twenty dolprotected from syphonage and waste iron pipe may be used, said iron pipe five feet outside of building, before lars per annum, payable in advance pipes leading from them, ventilated to extend one foot above grade of lot, being covered up must have all open on the first day of January of each y a special air pipe not less than the intercepting trap shall be supplied lings stopped up and filled with wa- year. No license shall be issued to mayor of the city of Medford, as mayany person or firm, to do a plumbing or of said city of Medford, Oregon, in which must be ventilated by a two-flush tank or water closet flush pipe; a fifteen-pound air test must be ap-inch pipe. Each and every trap shall no wash tray or basis waste shall be plied. When the plumber shall in the inspector of plumbing and drain- such mayor, do hereby make and isage. Any person or firm notifying sue this proclamation to the people the plumbing inspector that any job teen working hours after such notification, inspect the work, and if found the inspector a fee of one and one-number of votes cast at said election and the work done half per cent of the contract price and the total number of votes cast for such job and in case there be no for and against said charter amend-contract price, then one and one-half ment was as hereinbefore stated, and more than one lach fall between the scal trap and supplied with fresh the plumber, when the work may be trap and vent pipe.

The more than one lach fall between the scal trap and supplied with fresh the plumber, when the work may be that said amendment received an afternative majority of the total number.

The minimum for firmative majority of the total number. water from the nearest flush tank or covered up. No work shall be con-water closet flush pipe; said trap sidered ready for inspection until all any inspection shall be one dollar. her of votes cast at said election, and water closet flush pipe; said trap sidered ready for inspection until all any inspection shall be issued until that said amendment shall, and is, in

examination to be made within sixteen working hours after being notilow the top o, any fixtures they serve, all fixtures shall be separately and turned into any building or buildings plumbing work in the city of Medcharter of the city of Medcharter of the city of Medcharter of the city of Mednot more than one hundred dollars, terms and provisions of this ordi- do ordain as follows: Section 19. The inspector of plump- nance, after conviction for one offense, shall be deemed a new offense this ordinance, and where there is lating the plumbing ordinance, by a public sewer in any street or alley, using materials not in accordance which may be granted for such period days of such notice or conviction entered into by the city or any franwho shall fail, neglect or refuse to riod than ten years, except franchises remove said materials from any build- for street railways and for the purwithin ten days from said notice or its inhabitants, which may be grantconviction shall be punished by a fine ed for such period as the council or than one hundred dollars, and every day of such failure, refusal or neglect shall be considered a separate and

> Section 24. All work shall be reported by registered plumbers writing on forms furnished by the office of the inspector of plumbing twenty-four after and all water permits shall be signed by the inspector of plumbfore water is turned on any building for plumbing use. The inspector of plumbing and drainage is hereby auwork requiring inspection is not ready for inspection when the inspector has been notified to inspect the same. The inspector of plumbing and drainage shall give a receipt for all such fines collected, and pay the same to

DUTIES OF AACHITECTS AND BUILDERS

Section 25. It shall be the duty of any architect, or architects, builder six inches in diameter and shall be Lead traps and branch waste pipes shall not be less than the following several traps, in which case the size and must be of drawn lead of the main line must be increased as the floor with a cast brass flange. District any architect, or architects, builder and his deputies shall be appointed or builders, or other person or persons interested in any projected tender of the main line must be increased as the floor with a cast brass flange. deputy inspector of of habitation, in the city of Medford. thick, said flange to be properly soldered to lead pine and made perfect-shall have had at least two years' exply tight with a red lead putty conperience as a practical plumber, and plumbing and drainage of said city. Rubber washers shall not no person who shall be engaged in or that the inspector may examine said baving any pecuniary interest in any plans and specifications for his ap-URINALS.

Section 11. All urinals shall be supply business, shall be appoint- plans of ventilation, of water closets constructed of materials impervious ed to or retain the position of in- and sewers under buildings, drainage

# CITY NOTICES.

is hereby directed to refuse to grant The board of examiners shall con- a building permit until such

DUTIES OF INSPECTORS. Section 26. The inspector of plumbing (or his deputy) shall be in at-

> From 10:00 to 12:00 a. m. shall, upon being notified, examine

The assistant inspector of plumbplumbing in the dis-

The inspector of plumbing shall less than seventy-five per cent. to the city treasurer and take a EXAMINATION AND REGISTRA- ceipt therefor. He shall make to the city treasurer and take a remonthly report to the council, report Section 21. All persons engaged ing the number of jobs inspected and

Any person who shall violate any iners, and if approved by them, shall be subject to a fine of not less than register at the office of the inspector ten dollars nor more than one hun-of plumbing and drainage. When dred dollars for each and every of-

This ordinance shall become effect registration shall be made in the tive within five days after its appro-name of the co-partnership. Any val by the mayor. The above ordinance was

Welch aye, Merrick ave. Emerick

Approved March 21, 1910. W. H. CANON, Mayor. Attest:

ROBT. W. TELFER, City Recorder.

PROCLAMATION.

Whereas, there was submitted to the voters of the city of Medford, Oregon, at a special election held for that purpose on March 21, 1910, a proposed amendment to the charter the city of Medford, hereinafter set forth, and

Whereas, on he 22d day of March, 1910, the city recorder did in my presence canvas the votes given for and against said amendment; and Whereas, it was ascertained and determined upon said canvass that there were one hundred and eleven or them, any privy or cesspool upon laid with terra cotta pipe to curb, ex- proved by the inspector of plumb. forms furnished by the board of ex- (111) votes cast for and four (4) votes cast against said amendment, the total number of votes cast said election being one hundred and transacting a plumbing business with- fifteen (115), and that said amendin the jurisdiction of this ordinance ment received an affirmative majority of all the votes cast at said elec-

> tion. obedience and by virtue of the auof Medford, aforesaid, and do anher of votes cast at said election, and full force and effect from the date of Section 23. It shall be unlawful and that the following is the full text

chises be granted by said city. The people of the city of Medford

Section 1. That sub-section 42 of ection 25 of the charter of the city of Medford be amended so as to read as follows: 42. No franchise or contract shall

be granted for a longer period than extra fixtures, said fixtures must also than one trap before entering the the power to stop any or all work not the from the inspector of plumbing ten years, except street railway franbe vented or vent pipe must run to main drain. All bath tubs must have complying with the requirements of or who have been found guilty of viochises and franchises for supplying some accessible point for connection overflow if above first floor. gas to the city or its inhabitants, as the council or legal voters of said Section 100. No contract shall be

chise shall grant any exclusive right or rights. Done at Medford, Oregon, this 22d

day of March, A. D. 1910. W. H. CANON, Mayor, Attest:

ROBT. W. TELFER. Recorder.

Writing and paying for a want ad. are matters of a few minutes and a you want which would be worth getting at so slight cost?

# **Medford Shoe** Shining Parlor OH, HERE WE ARE AT LAST!

For ladies, gents, children, this is the place where you will save time and money by getting your shoes shined by an experienced artist. Oiling and dyeing is my specialty. Now, don't forget the place, No. 4 South Central aveme. Open from 7 a. m. to 8 p. m.; Sundays till 2 p. m. The const Champion Bootblack.

V. W. HOWARD, Prop.